



# HEAVY DUTY DIESEL XHD-7 10W-30

**AMERICA'S CHOICE<sup>®</sup> Heavy-Duty Diesel XHD-7 10W-30 Motor Oil** is specifically engineered to meet the latest requirements for EGR/EPF engines. Meets or exceeds API Service CJ-4/SM as well as older API categories CI-4 Plus, CI-4 and CH-4. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

Since America's Choice<sup>®</sup> is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

## TYPICAL PROPERTIES

AMERICAS CHOICE <sup>®</sup>	SAE	10W-30
API Service		CJ-4 / SM
Kinematic Viscosity		
cSt @ 40°C		81.8
cSt @ 100°C		12.2
Viscosity Index		146
CCS Viscosity		
cP @ -25°C		6600
Flash Point, °C		222
Pour Point, °C		-33
Specific Gravity 15.6°C (60°F)		0.868
Color (ASTM)		4.5
TBN		9.5
Sulfated Ash, wt%		0.98

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYMHB