



# HEAVY DUTY DIESEL 15W-40

**AMERICA'S CHOICE® Heavy Duty Diesel 15W-40 Motor Oil** is specifically engineered to meet the needs of engines requiring API Service Category CJ-4 / SL. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline, or propane engines.

Since America's Choice® is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

## TYPICAL PROPERTIES

PERFORMANCE PLUS®	SAE	15W-40
API Service		CJ-4 / SL
Kinematic Viscosity		
cSt @ 40°C		117.8
cSt @ 100°C		15.7
Viscosity Index		141
CCS Viscosity		
cP @ -20°C		6300
Flash Point, °C		232
Pour Point, °C		-33
Specific Gravity 15.6°C (60°F)		0.872
Color (ASTM)		L 3.5
TBN		9.4
Sulfated Ash, wt%		0.99

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BZ12L