



SYNTHETIC BLEND PASSENGER CAR MOTOR OIL

AMERICA'S CHOICE[®] Synthetic Blend Passenger Car Motor Oils are specially formulated with a combination of Group II and Group III base oils plus state-of-the art performance additives. They are engineered to exceed the demands of turbocharged and high-power, high-efficiency gasoline, propane, and natural gas engines in the latest model passenger cars and light duty trucks. SAE 5W-20 and 5W-30 grades are Resource Conserving motor oils that exceed API service SN and ILSAC Starburst GF-5, as well as older service categories SM, SL, and previous ILSAC categories.

Since America's Choice[®] is made from recycled and re-refined used motor oil, it satisfies recent Federal directives for government agencies to use recycled/recovered materials, including:

- Executive Order 13423, signed in 2007 by President Bush, mandates "in Federal agency acquisitions of goods and services use of sustainable environmental practices, including acquisition of bio-based, environmentally preferable, energy-efficient, water-efficient, and recycled-content products"
- Section 6002 of RCRA that requires federal agencies to "procure such items composed of the highest percentage of recovered materials practicable"
- Federal Regulation 23.4 that requires Federal Agencies to "use recovered materials to the maximum extent practicable"

TYPICAL PROPERTIES

PERFORMANCE PLUS [®]	SAE	5W-20	5W-30
API Service		SN	SN
ILSAC		GF-5	GF-5
Kinematic Viscosity			
cSt @ 40°C		50.0	62.1
cSt @ 100°C		8.6	10.4
Viscosity Index		150	157
CCS Viscosity			
cP @ -30°C		6000	6300
Evaporative Loss, NOACK, wt%		<15	<15
Specific Gravity 15.6°C (60°F)		0.862	0.861
Flash Point, °C		218	220
Pour Point, °C		-39	-39
Color (ASTM)		3.0	3.0
Sulfated Ash, wt%		0.92	0.92

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYU74