


America's Choice®



Heavy Duty Diesel 15W-40 XHD-7

America's Choice® Heavy Duty 15W-40 Diesel Motor Oil meets or exceeds older API categories CI-4 PLUS, CI-4 and CH-4, Mack EO-O Premium Plus, Cummins CES 20081, Caterpillar ECF-1 and ECF-3, Volvo VDS-4, Detroit Diesel PGOS 93K218 and Ford standards for performance and protection. Recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline or propane engines.

Safety-Kleen's closed loop re-refining process takes used motor oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined motor oil. Re-refining motor oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

TYPICAL PROPERTIES

<i>America's Choice®</i>	SAE 15W-40
API Service	CJ-4/SM
Specific Gravity	
@ 15.6 °C	0.89
Viscosity	
cSt @ 40 °C	118
cSt @ 100 °C.....	15.7
Viscosity Index	140
CCS Viscosity	
cP @ -20 °C	6,700
Flash Point, °C.....	217
Pour Point, °C	-33
Color (ASTM)	3.5
TBN	9.5
Sulfated Ash, % Mass	0.98

Note: The values shown are representative of current production and may vary within modest ranges.

Available in bulk



Safety-Kleen Systems, Inc.
safety-kleen.com, ac-rerefined.com

Customer Service 1-800-525-5739

5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

