


# America's Choice®



## Heavy Duty Diesel Motor Oils

**America's Choice®** Heavy Duty Diesel Motor Oils are refined to reduce wear and tear on valve trains and rings while preventing sludge and carbon deposits. Recommended for naturally aspirated, turbo or supercharged diesel engines, they meet or exceed requirements for Mack EO-M Plus and Cummins CES 200073 (10W30 and 15W40) specifications. Fluids also recommended for power shift transmissions specifying ALLISON C-3/C-4, CAT TO-2 fluids and mobile equipment hydraulic systems specifying engine oils.

Safety-Kleen's closed loop re-refining process takes used motor oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined motor oil. Re-refining motor oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

### TYPICAL PROPERTIES

<b>America's Choice®</b>	<b>SAE</b>	<b>10W-30</b>	<b>15W-40</b>	<b>10W</b>	<b>30</b>	<b>40</b>	<b>50</b>
API Service .....	CI-4/SJ	CI-4/SL	CF	CI-4/SJ	CI-4/SJ	CI-4/SJ	CI-4/SJ
Also recommended for older engines specifying .....	API CH-4, CG-4, CF/SH SJ, Mack EO-L, EO-K2 & Cummins 200076	API CH-4, CG-4, CF/SH, SJ, Mack EO-L, EO-K2 & Cummins 200076	API CF	API CF	API CF	API CF	API CF
Specific Gravity							
@ 15.6 °C .....	.878	.882	.876	.886	.897	.896	
Viscosity							
cSt @ 40 °C .....	75	116	43	107	142	207	
cSt @ 100 °C .....	11.5	15.5	6.5	11.9	14.5	18.0	
Viscosity Index .....	146	141	100	100	100	95	
CCS Viscosity							
cP @ -20 °C .....	3,300	NA	NA	NA	NA	NA	NA
cP @ -15 °C .....	NA	3,300	NA	NA	NA	NA	NA
cP @ -10 °C .....	NA	NA	NA	NA	NA	NA	NA
Flash Point, °C .....	208	215	205	220	230	236	
Pour Point, °C .....	-33	-33	-39	-18	-12	-9	
Color (ASTM) .....	3.5	3.5	3.0	4.0	4.0	4.0	
TBN .....	9.5	9.5	9.5	9.5	9.5	9.5	
Sulfated Ash, wt% .....	1.2	1.2	1.2	1.2	1.2	1.2	

*Note: The values shown are representative of current production and may vary within modest ranges.*

**Available in bulk (15W-40  
also available in quart bottles)**



Safety-Kleen Systems, Inc.  
safety-kleen.com, ac-rerefined.com

**Customer Service 1-800-525-5739**  
5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

