

America's Choice®



Premium Heavy Duty Diesel 15W-40 PLD-3

America's Choice® Premium Heavy Duty 15W-40 Diesel Motor Oil provides unmatched engine protection while preventing sludge and carbon deposits. Meets manufacturer requirements for EGR engines requiring premium PLD-3 motor oil and is recommended for naturally aspirated, turbocharged or supercharged diesel, gasoline or propane engines. Meets or exceeds requirements of Cummins CES 200078, Caterpillar ECF-1, Detroit Diesel Power Guard 92K214, Mack EO-N Premium Plus '03, Volvo VDS-3. Also suitable for use in Allison C-3/C-4 and CAT TO-2 power shift transmissions.

Safety-Kleen's closed loop re-refining process takes used motor oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined motor oil. Re-refining motor oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

TYPICAL PROPERTIES

<i>America's Choice®</i>	SAE 15W-40
API Service	CI-4 Plus/SL
Also recommended for older engines specifying	CI-4, CH-4, CG-4, CF-4, CF/SH, SJ, Mack EO-M, EO-L, EO-K2
Specific Gravity @ 15.6 °C	0.887
Viscosity cSt @ 40 °C	116
cSt @ 100 °C.....	15.5
Viscosity Index	140
CCS Viscosity cP @ -20 °C	6,600
Flash Point, °C.....	216
Pour Point, °C	-33
Color (ASTM)	5
TBN	10.5
Sulfated Ash, % Mass	1.37

Note: The values shown are representative of current production and may vary within modest ranges.

Available in bulk and quart bottles



Safety-Kleen Systems, Inc.
safety-kleen.com, ac-rerefined.com

Customer Service 1-800-525-5739

5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

