


America's Choice®



Zinc Free Anti-Wear Hydraulic Oils

America's Choice® Zinc Free Anti-Wear Hydraulic Oils are the ideal solution for industrial and mobile hydraulic systems. Containing anti-wear and rust inhibiting additives, it remains stable when exposed to moisture and extreme temperatures. Meets Cincinnati Machine P-68, P-69 AND P-70, Dennison HF-0, HF-1, HF-2, Eaton/Vickers M-2950-S, I-286-S, Ford M6C32 and General Motors LS-2 specifications.

Safety-Kleen's closed loop re-refining process takes used oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined oil. Re-refining oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

TYPICAL PROPERTIES

| <i>America's Choice®</i> | 32 | 46 | 68 |
|-------------------------------------|-------------|-------------|-------------|
| Specific Gravity | | | |
| @ 15.6 °C | .865 | .868 | .870 |
| Viscosity | | | |
| cSt @ 40 °C | 32 | 44 | 66 |
| cSt @ 100 °C..... | 5.45 | 6.8 | 8.9 |
| Viscosity Index | 109 | 109 | 109 |
| Flash Point, °C..... | 190 | 200 | 214 |
| Pour Point, °C | -36 | -33 | -30 |
| Color (ASTM) | 1.0 | 1.5 | 3.0 |
| Oxidation, ASTM D943, HRS | 3000 | 3000 | 2000 |
| Rust Protection, ASTM D665 A&B..... | Pass | Pass | Pass |
| Demulsibility, ASTM D1401 | 40/37/3(15) | 40/37/3(15) | 40/37/3(15) |
| Copper Corrosion, ASTM D130 | 1A | 1A | 1A |

Note: The values shown are representative of current production and may vary within modest ranges.

Available in bulk



Safety-Kleen Systems, Inc.
safety-kleen.com, ac-rerefined.com

Customer Service 1-800-525-5739

5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

