



EP INDUSTRIAL GEAR OIL

PERFORMANCE PLUS[®] EP Industrial Gear Oils are specifically formulated to hold up under extreme high pressure in all types of gear sets excluding built-in variable speed friction drives. Approved for use in Chrysler and General Motors. Increase the life of your heavily loaded or shock loaded bearings and gear sets with EP Industrial Gear Oils.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI base oils.

For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.

TYPICAL PROPERTIES

| PERFORMANCE PLUS [®] | ISO GRADE | 68 | 100 | 150 | 220 | 320 | 460 |
|--------------------------------|-----------|-------|-------|-------|-------|-------|-------|
| AGMA Grade | | 2EP | 3EP | 4EP | 5EP | 6EP | 7EP |
| Color | | L 3.0 | L 3.5 | L 3.5 | L 3.5 | L 4.0 | L 5.5 |
| Specific Gravity 15.6°C (60°F) | | 0.872 | 0.875 | 0.881 | 0.885 | 0.888 | 0.892 |
| Kinematic Viscosity | | | | | | | |
| cSt @ 40°C | | 66.2 | 100.5 | 152.0 | 221.6 | 320.0 | 460.0 |
| cSt @ 100°C | | 8.9 | 11.8 | 15.4 | 19.5 | 28.0 | 30.0 |
| Viscosity Index | | 109 | 106 | 102 | 100 | 99 | 95 |
| Flash Point, °C | | 233 | 238 | 242 | 246 | 248 | 252 |
| Pour Point, °C | | -30 | -27 | -18 | -12 | -9 | -6 |
| Demulsibility D1401 | | Pass | Pass | Pass | Pass | Pass | Pass |
| Timken OK Load, lbs | | 65 | 65 | 65 | 65 | 65 | 65 |
| FZG Pass Stage | | 12 | 12 | 12 | 12 | 12 | 12 |
| Copper Corrosion | | 1B | 1B | 1B | 1B | 1B | 1B |

Note: Values shown above are representative of current production and may vary within modest ranges.

Rev. BYU41