



GL-5 GEAR OIL

PERFORMANCE PLUS[®] GL-5 Gear Oils are premium quality multi-purpose gear oils formulated to minimize gear friction, reduce corrosion, and prevent the formation of sludge. It meets or exceeds API GL-5, Mack GO-G / GO-H performance standards for all vehicles and heavy-duty equipment differentials, final drives, manual transmissions and gearboxes. Also suitable for industrial gearboxes specifying US Steel 224.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI base oils.

For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.

TYPICAL PROPERTIES			
PERFORMANCE PLUS [®]	SAE	80W-90	85W-140
API Service		GL - 5	GL - 5
Kinematic Viscosity			
cSt @ 40°C		145.4	341.3
cSt @ 100°C		15.2	25.6
Viscosity Index		106	97
Brookfield Viscosity			
cP @ -26°C		105000	-
cP @ -12°C		-	60000
Color		L 3.5	L 4.5
Specific Gravity 15.6°C (60°F)		0.885	0.896
Flash Point, °C		214	218
Pour Point, °C		-30	-12

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BYM66