



HEAVY DUTY DIESEL 15W-40 CI-4

PERFORMANCE PLUS[®] Heavy Duty Diesel 15W-40 CI-4 / SL Motor Oil is engineered to reduce wear and tear on valve trains and rings while preventing sludge and carbon deposits. Recommended for naturally aspirated, turbocharged, or supercharged diesel, gasoline, and propane engines, they meet or exceed the performance requirements for Mack EO-M Plus, Cummins CES 20078, Volvo VDS / VDS-2, Caterpillar ECF-1, and power shift transmissions specifying Allison C-3 / C-4, and CAT TO-2.

The foundation of Performance Plus Oils are Safety-Kleen's hydro-treated, high VI, Group II base oils. **For more than 30 years, Safety-Kleen oil products have performed without fail in the most severe operating conditions.**

TYPICAL PROPERTIES

PERFORMANCE PLUS [®]	SAE	15W-40
API Service		CI-4 / SL
Kinematic Viscosity		
cSt @ 40°C		116.2
cSt @ 100°C		15.6
Viscosity Index		142
CCS Viscosity		
cP @ -20°C		6200
Flash Point, °C		228
Pour Point, °C		-33
Specific Gravity 15.6°C (60°F)		0.872
Color (ASTM)		L 3.0
TBN		10.2
Sulfated Ash, wt%		1.2

Note: Values shown above are representative of current production and may vary within modest ranges

Rev. BZ12L