

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 04/13/2023 Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Performance Plus ICE BREAKER EXTREME Windshield Washer Fluid, Winter -20 Blend

Product Code: 6170, 617055, 6560, 6561

Synonyms: Glass and Surface Cleaner; Flammable Windshield Washer Fluid

SDS No: 820468

1.2. **Intended Use of the Product**

Cleaning glass surfaces

1.3. Name, Address, and Telephone of the Responsible Party

Supplier (in Canada) Manufacturer

Safety-Kleen Canada, Inc. Safety-Kleen Systems, Inc.

25 Regan Road 42 Longwater Drive Brampton, Ontario, Canada L7A 1B2

Norwell, MA 02061-9149

1-800-669-5740

www.safety-kleen.com

Emergency Number : 1-800-468-1760

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Emergency Telephone Number

GHS-US/CA Classification

Flammable liquids Category 3	H226
Acute toxicity (oral) Category 3	H301
Acute toxicity (dermal) Category 3	H311
Acute toxicity (inhalation:dust,mist) Category 4	H332
Specific target organ toxicity (single exposure) Category 1	H370
Specific target organ toxicity — Single exposure, Category 3,	H336
Narcosis	

2.2. **Label Elements**

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)









Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H226 - Flammable liquid and vapor.

H301+H311 - Toxic if swallowed or in contact with skin.

H332 - Harmful if inhaled.

H336 - May cause drowsiness or dizziness.

H370 - Causes damage to organs (central nervous system, optic nerve).

Precautionary Statements (GHS-US/CA): P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating, and lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges. P260 - Do not breathe vapors, mist, or spray.

04/13/2023 EN (English US) SDS#: 820468 1/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor.

P312 - Call a POISON CENTER or doctor if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P330 - Rinse mouth.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Methanol	METHYL ALCOHOL / Wood	(CAS-No.) 67-56-1	31.76 –	Flam. Liq. 2, H225
	alcohol / Methyl hydroxide / Carbinol / Methyl alcohol		40	Acute Tox. 3 (Oral), H301
	Carbinor / Metrryr accorbi			Acute Tox. 3 (Dermal), H311
				Acute Tox. 3 (Inhalation), H331
				STOT SE 1, H370
				STOT SE 3, H336

Full text of H-statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.

Skin Contact: Immediately remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Immediately call a poison center or doctor/physician.

Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.

Ingestion: Contains methanol, administration of pure ethanol or fomepizole may be required to treat methanol poisoning. Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor.

04/13/2023 EN (English US) SDS#: 820468 2/10

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Ocular toxicity to potentially include blindess. May cause drowsiness and dizziness. Causes damage to organs (optic nerve, central nervous system) (Oral). Harmful if inhaled. Toxic if swallowed. Toxic in contact with skin.

Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

Skin Contact: This material is toxic in small amounts through skin contact, and can cause adverse health effects or death. This material may be absorbed through the skin and eyes.

Eye Contact: May cause slight irritation to eyes.

Ingestion: This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death. This material is toxic in small amounts orally, and can cause adverse health effects or death.

Chronic Symptoms: May cause damage to organs (Optic nerve. Central nervous system) through prolonged or repeated exposure. Blindness.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable liquid and vapor.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Eliminate ignition sources first, then ventilate the area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Remove ignition sources. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

04/13/2023 EN (English US) SDS#: 820468 3/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material. Use only non-sparking tools. Do not take up in combustible material such as: saw dust or cellulosic material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Do not breathe vapors, spray, mist. Do not get in eyes, on skin, or on clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Handle empty containers with care because they may still present a hazard.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Cleaning glass surfaces

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Methanol (67-56-1)		
USA ACGIH	ACGIH OEL TWA [ppm]	200 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	250 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure
		by the cutaneous route
USA ACGIH	BEI (BLV)	15 mg/L Parameter: Methanol - Medium: urine - Sampling
		time: end of shift (background, nonspecific)
USA OSHA	OSHA PEL (TWA) [1]	260 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	200 ppm
USA NIOSH	NIOSH REL (TWA)	260 mg/m³
USA NIOSH	NIOSH REL TWA [ppm]	200 ppm
USA NIOSH	NIOSH REL (STEL)	325 mg/m ³
USA NIOSH	NIOSH REL STEL [ppm]	250 ppm
USA IDLH	IDLH [ppm]	6000 ppm
Alberta	OEL STEL	328 mg/m ³
Alberta	OEL STEL [ppm]	250 ppm
Alberta	OEL TWA	262 mg/m³
Alberta	OEL TWA [ppm]	200 ppm
British Columbia	OEL STEL [ppm]	250 ppm
British Columbia	OEL TWA [ppm]	200 ppm
Manitoba	OEL STEL [ppm]	250 ppm
Manitoba	OEL TWA [ppm]	200 ppm
New Brunswick	OEL STEL	328 mg/m³
New Brunswick	OEL STEL [ppm]	250 ppm

04/13/2023 EN (English US) SDS#: 820468 4/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

New Brunswick	OEL TWA	262 mg/m³
New Brunswick	OEL TWA [ppm]	200 ppm
Newfoundland & Labrador	OEL STEL [ppm]	250 ppm
Newfoundland & Labrador	OEL TWA [ppm]	200 ppm
Nova Scotia	OEL STEL [ppm]	250 ppm
Nova Scotia	OEL TWA [ppm]	200 ppm
Nunavut	OEL STEL [ppm]	250 ppm
Nunavut	OEL TWA [ppm]	200 ppm
Northwest Territories	OEL STEL [ppm]	250 ppm
Northwest Territories	OEL TWA [ppm]	200 ppm
Ontario	OEL STEL [ppm]	250 ppm
Ontario	OEL TWA [ppm]	200 ppm
Prince Edward Island	OEL STEL [ppm]	250 ppm
Prince Edward Island	OEL TWA [ppm]	200 ppm
Québec	VECD (OEL STEL)	328 mg/m³
Québec	VECD (OEL STEL) [ppm]	250 ppm
Québec	VEMP (OEL TWA)	262 mg/m³
Québec	VEMP (OEL TWA) [ppm]	200 ppm
Saskatchewan	OEL STEL [ppm]	250 ppm
Saskatchewan	OEL TWA [ppm]	200 ppm
Yukon	OEL STEL	310 mg/m³
Yukon	OEL STEL [ppm]	250 ppm
Yukon	OEL TWA	260 mg/m³
Yukon	OEL TWA [ppm]	200 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/Local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gas detectors should be used when toxic gases may be released.

Personal Protective Equipment: Safety glasses with side-shields. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection. Face shield.











Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Safety glasses with side-shields. Faceshield as determined by task.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid
Appearance : Blue
Odor : Alcohol

Odor Threshold: No data availablepH: No data availableEvaporation Rate: No data available

04/13/2023 EN (English US) SDS#: 820468 5/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Melting Point No data available **Freezing Point** -20 °F (-28.89 °C) **Boiling Point** 81.7 °C (179.06 °F) **Flash Point** 36.7 °C (98.06 °F) **Auto-ignition Temperature** No data available **Decomposition Temperature** No data available **Flammability** Not applicable **Lower Flammable Limit** No data available **Upper Flammable Limit** No data available **Vapor Pressure** No data available Relative Vapor Density at 20°C No data available **Relative Density** 0.96 (water =1) **Specific Gravity** No data available Solubility No data available **Partition Coefficient: N-Octanol/Water** No data available Viscosity No data available

VOC content : 40 %

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

10.2. Chemical Stability:

Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides (CO, CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Toxic if swallowed.

Acute Toxicity (Dermal): Toxic in contact with skin.
Acute Toxicity (Inhalation): Harmful if inhaled.

LD50 and LC50 Data:

Performance Plus Ice Breaker Windshield Washer Fluid – Extreme Winter		
ATE US/CA (oral)	250.00 mg/kg body weight	
ATE US/CA (dermal)	750.00 mg/kg body weight	
ATE US/CA (dust, mist)	1.25 mg/L/4h	

Skin Corrosion/Irritation: Not classified Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Causes damage to organs (central nervous system, optic nerve). May cause

drowsiness or dizziness.

Aspiration Hazard: Not classified

04/13/2023 EN (English US) SDS#: 820468 6/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Symptoms/Injuries After Inhalation: High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

Symptoms/Injuries After Skin Contact: This material is toxic in small amounts through skin contact, and can cause adverse health effects or death. This material may be absorbed through the skin and eyes.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: This material contains methanol, which, when ingested, may cause acidosis and ocular toxicity ranging from diminished visual capacity to complete blindness, and possible death. This material is toxic in small amounts orally, and can cause adverse health effects or death.

Chronic Symptoms: May cause damage to organs (Optic nerve. Central nervous system) through prolonged or repeated exposure. Blindness.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Methanol (67-56-1)		
LD50 Oral Rat	6200 mg/kg	
LD50 Dermal Rabbit	15840 mg/kg	
LC50 Inhalation Rat	128.2 mg/L/4h	
LC50 Inhalation Rat	22500 ppm (Exposure time: 8 h)	
ATE US/CA (oral)	100.00 mg/kg body weight	
ATE US/CA (dermal)	300.00 mg/kg body weight	
ATE US/CA (gas)	700.00 ppmV/4h	
ATE US/CA (vapors)	3.00 mg/L/4h	
ATE US/CA (dust, mist)	0.50 mg/L/4h	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

Methanol (67-56-1)	
LC50 Fish 1	28200 mg/L (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 Fish 2	> 100 mg/L (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and Degradability

<u> </u>	
Performance Plus Ice Breaker Windshiel	d Washer Fluid – Extreme Winter
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Performance Plus Ice Breaker Windshield Washer Fluid – Extreme Winter		
Bioaccumulative Potential	Not established.	
Methanol (67-56-1)		
BCF Fish 1	(10)	
Partition coefficient n-octanol/water	-0.77	
(Log Pow)		

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment.

04/13/2023 EN (English US) SDS#: 820468 7/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

04/13/2023 EN (English US) SDS#: 820468 8/10

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

14.1. In Accordance with DOT

Proper Shipping Name : FLAMMABLE LIQUIDS, N.O.S. (CONTAINS : Methanol)

Hazard Class : 3

Identification Number : UN1993

Label Codes : 3 **Packing Group** : 111 **ERG Number** : 128



Proper Shipping Name : FLAMMABLE LIQUIDS, N.O.S. (CONTAINS: Methanol)

Hazard Class : 3

Identification Number : UN1993

Label Codes : 3 **Packing Group** : 111 EmS-No. (Fire) : F-E EmS-No. (Spillage) : S-E



Proper Shipping Name : FLAMMABLE LIQUIDS, N.O.S. (CONTAINS: Methanol)

Hazard Class : 3 **Identification Number** : UN1993

: 3 **Label Codes Packing Group** : 111 **ERG Code (IATA)** : 3L

In Accordance with TDG 14.4.

Proper Shipping Name : FLAMMABLE LIQUIDS, N.O.S. (CONTAINS: Methanol)

Hazard Class : 3 **Identification Number** : UN1993

Label Codes : 3 **Packing Group** : 111



SECTION 15: REGULATORY INFORMATION

15.1. **US Federal Regulations**

Performance Plus Ice Breaker Windshield Washer Fluid – Extreme Winter			
SARA Section 311/312 Hazard Classes Health hazard - Specific target organ toxicity (single or reperence exposure)			
Physical hazard - Flammable (gases, aerosols, liquids, or s			
	Health hazard - Acute toxicity (any route of exposure)		
Methanol (67-56-1)			
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active			
CERCLA RQ 5000 lb			
SARA Section 313 - Emission Reporting 1 %			

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

CAS-No.	Name	Percent by Weight
67-56-1	Methanol	31.76 – 40%

15.2. **US State Regulations**

California Proposition 65

WARNING: This product can expose you to Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Methanol (67-56-1)		Х		

04/13/2023 EN (English US) SDS#: 820468 9/10



















Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Methanol (67-56-1)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

15.3. Canadian Regulations

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest

: 09/26/2022

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

NFPA Health Hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA Fire Hazard

3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient

temperature conditions.

NFPA Reactivity Hazard

: 0 - Material that in themselves are normally stable, even

under fire conditions.

d is designed only as guidance

The information contained herein is correct to the best of our knowledge, information, and belief and is designed only as guidance for the handling, use, processing, storage, transportation, disposal, and release of the product. User assumes all risks incident to use of this product and shall determine the quality and suitability of the product for its use. Supplier offers no warranty, express or implied, whatsoever, including warranties of merchantability or fitness for a particular purpose or otherwise, and specifically disclaims any and all liability for incidental, consequential, or other damages arising out the use or misuse of the product. The information provided relates only to the specific material provided and may not be valid if used in combination with any other materials or process, unless specified herein.

NA GHS SDS 2015 (Can, US)

04/13/2023 EN (English US) SDS#: 820468 10/10